

GK10DO...GK80DO

No.	Dimensione (mm)												Load rating(kN)		Peso ≈kg	Stock
	d	B	dk	C1	d2	h2	L4 max	d4	d3	L8	min a° ≈	Coefficienti di carico kN/dinamico	Carico nominale kN/statico			
GK17DO	17	14	25	11	46	35	58	24	4	2	0.3	10	21	40	0.19	✓
GK20DO	20	16	29	13	53	38	64.5	27.5	4	2	0.3	9	30	54	0.23	✓
GK25DO	25	20	35.5	17	64	45	77	33.5	4	3	0.6	7	48	72	0.43	✓
GK15DO	15	12	22	10	40	31	51	21	4	2	0.3	8	16	32	0.12	✓
GK10DO	10	9	16	7	29	24	38.5	15	3	1.5	0.3	12	8.1	15	0.041	✓
GK12DO1)	12	10	18	8	34	27	44	17.5	3	1.5	0.3	10	10	21	0.066	✓
GK30DO	30	22	40.7	19	73	51	87.5	40	4	3	0.6	6	62	95	0.64	✓
GK35DO	35	25	47	21	82	61	102	47	4	3	0.6	6	79	125	0.96	✓
GK40DO	40	28	53	23	92	69	115	52	4	4	0.6	7	99	156	1.3	✓
GK45DO	45	32	60	27	102	77	128	58	6	4	0.6	7	127	208	1.8	✓
GK50DO	50	35	66	30	112	88	144	62	6	4	0.6	6	156	250	2.5	✓
GK60DO	60	44	80	38	135	100	167.5	70	6	4.5	1	6	245	390	3.9	✓
GK70DO	70	49	92	42	160	115	195	80	6	6	1	6	313	510	6.6	✓
GK80DO	80	55	105	47	180	141	231	95	6	6	1	6	400	620	8.7	✓