

SS6200 Series

Cuscinetto n.	Dimensioni (millimetro)				Ball Complement	Maximum speed (r/min)		Il peso Kg/pcs
	D	d	B	NO		Size	Grease	
S 623	10	3	4	7	1.588	38000	48000	0.0015
S 624	13	4	5	6	2.381	36000	45000	0.0032
S 625	16	5	5	8	2.381	32000	40000	0.0048
S 626	19	6	6	6	3.969	28000	36000	0.0081
S 627	22	7	7	7	3.969	26000	34000	0.013
S 628	24	8	8	7	3.969	24000	32000	0.017
S 629	26	9	8	7	4.5	22000	30000	0.02
S 6200	30	10	9	8	4.763	19000	26000	0.032
S 6201	32	12	10	7	5.953	18000	24000	0.037
S 6202	35	15	11	8	5.953	17000	22000	0.045
S 6203	40	17	12	8	6.747	16000	20000	0.066
S 6204	47	20	14	8	7.938	14000	18000	0.106
S 6205	52	25	15	9	7.938	12000	16000	0.128
S 6206	62	30	16	9	9.525	10000	13000	0.199
S 6207	72	35	17	9	11.112	8800	10000	0.287
S 6208	80	40	18	9	12	7700	9200	0.367
S 6209	85	45	19	10	12	6800	8200	0.416
S 6210	90	50	20	10	12.7	6100	7300	0.462
S 6211	100	55	21	10	14.288	5500	6600	0.602
S 6212	110	60	22	10	15.081	5000	5500	0.804
S 6213	120	65	23	10		5400	6400	0.99
S 6214	125	70	24	11		5100	6000	1.34